

Method of Measuring Power Consumption of Stirrers,
by S. Nagata, T. Yokoyama, 11 pp.
Kagaku Kagaku
JAPANESE, per. Chem Eng (Japan), Vol XX, 1956,
pp 272-279.

Assoc Tech Sv 52E12J

Sci
Aug 58

70,763

Applications of Radioisotopes to the Measure-
ment of Flow Patterns of Liquids in a Mixing
Tank, by S. Aiba, 13 pp.

Kagaku Kogaku
JAPANESE, per, Chem Eng Japan, Vol XX, No 6,
1956, pp 280-287.

Sci

44-51512
Chem Tech Serv

Cyanic Acid Synthesis in a Fluidized Bed Reactor,
by M. Nakagawa.
JAPANESE, per, Kagaku Kogyo, No 9, 1956, ~~pp 29-33~~
pp 29-33.
NASA TT F-8496

Sci - Chem
Mar 64
U.S. GOVERNMENT ONLY

251,944

Studies of Turbulent Flow in Agitating Tank, by
K. Yamamoto, E. Kawahigashi, 13 pp.

JAPANESE, per, Kagaku Kagaku, Vol XX, No 12, 1956,
pp 685-694.

ASST Tech Serv
28K28J

Sci- Phys
OTS I, 9
Jun 59

89,538

Heat Transfer Coefficients of Diatomite
Slurries, by Eiji Hirai.
JAPANESE, per, Kagaku Kagaku, Vol 21, 1957,
pp 25-31. 9232389
AEC UCRL-Tr-1313

Sci/482
May 66

500,433

Classification Efficiency of a Two-Stage Hydraulic
Cyclone, by Naoya Yoshioka, Yutaka Hotta, Tsutomu
Mizutani, 13 pp.

Kagaku Kagaku
JAPANESE, per, Chem Eng Soc Japan, Vol XXI, 1957,
pp 32-36.

AEC Tr 3216

Sci - Eng

May 58

64, 826

A Study of Mixing of Highly Viscous Liquids, by S.
Kagata, M. Yamamoto, T. Yokoyama, 14 pp.

JAPANESE, per, Kagaku Kogaku, Vol. XXI, No 5, 1957,
pp 278-286.

Asso Tech Serv
32K28J

Sci - Phys
OTS I, 9
Jun 59

Mining of Potatoes in Several Types of Mines,
by T. Yano, 17 pp

JAPANESE, par, Kagaku Kagaku, Vol. XXI,
No 7, 1957, pp 425-425.

ANHS, Hawaii

LA-1672

AFSC-1672 (7210746)

2/11, 520

Sel. - Chem

Sep 62

ALA M 10021

Tanaka, T. and Yada, S.
KINETICS OF THE CATALYTIC HYDROGENATION
OF 2-ETHYLHEXENE-2-AL-1 IN THE VAPOR PHASE.
[1962] [9]p. 2 refs.
Order from SLA \$1.10

62-18927

Trans. of Kagaku [Kogaku] (Japan) 1957, v. 21,
p. 721-726.

DESCRIPTORS: *Plasticizers, Ethyl radicals, Cyclo-
hexenes, *Aldehydes, Vapors, Hydrogenation, Cataly-
sis, Reaction kinetics, Graphic analysis, Tables.

Reaction rate equations for isobaric gaseous hydrogenation of 2-ethylhexene-2-al-1 were obtained. An equation was deduced for obtaining the optimum reaction temperature for each rate of conversion. By effective application, the most economical industrial apparatus can be designed. The results of a sample experiment are shown.
(Chemistry--Physical, TT, v. 19, no. 1)

62-18927

I. Tanaka, T.
II. Yada, S.

Office of Technical Services

The Influence of the Number of Impacts in
Pulverization, by Y. Nakagawa, K. Matsui, 15 pp.

JAPANESE, per, Kagaku Kogaku, Vol XXI, 1957,
pp 810-816.

AEC MP Tr-541

Sci - Nuc Phys
May 61

150,373

On the Characteristics of a Centrifuge, by
Y. Mori, R. Aoki, A. Saito, T. Tsuchida, M. Ebata,
19 pp.

Kagaku Kagaku
JAPANESE, por, Chemical Engineering, Vol XXII, 1958,
pp 7-15.

AEC 3342

Sci - Engr

Oct 58

74 102

(2113-H)

Carbons and Organic Semi-Conductors, by
Hideo Akamatsu, 19 pp.

JAPANESE, per, Kagaku to Engyo, No 7, 1958,
pp 39-45.

US JPRS 1-506-H

PB - Japan

Sci - Physics, semiconductors

Jan 59

80,599

Motion of Water in a Hydraulic Cyclone, by
H. Choshi, S. Masada, 16 pp.

Kagaku Kagaku
JAPANESE, per, Chemical Engineering, Vol XXII,
1958, pp 200-207.

AEC ~~44-3~~ 3343

Sci - Engr

Oct 58

74,604

Solubility of Chlorine Gas in Concentrated Sodium
Chloride Solutions, by Kenyuki Yokota, 12 pp.

JAPANESE, per: Kagaku Kagaku, Vol XXII, 1958,
pp 476-482.

SLA 59-15634

Sci
Dec 59
Vol 2, No 5

103,782